

EXPANDABLE BRAIDED SLEEVE - REEL

PART NR.

See dimensions table

COUNTRY OF ORIGIN

China

STANDARDS

REACH and RoHS compliant

Halogen free

Flammability: VW-1

UL listed

CHARACTERISTICS

- Our expandable sleeve is flame retardant and halogen free
- It offers durable abrasion resistance in a wide range of industrial applications
- The open weave structure allows an easy installation on a bundle of hoses or cables, even with bulky or large size
- Totally expanded sleeve can reach at least 1.5 times of the initial dimension
- It is ideal for application in wire harnesses, automatic equipment, railway and general manufacturing industry, where wire and cable are required to have a robust and durable protection
- Cutting tool: hot knife

PHOTO / TECHNICAL DRAWING



DIMENSIONS

Part nr.	Nom. size mm	Bundle range mm	Mtrs/reel
EBS-003BK	3	1 - 6	1000
EBS-003OR	3	1 - 6	1000
EBS-006BK	6	3 - 9	500
EBS-006OR	6	3 - 9	500
EBS-008BK	8	5 - 16	350
EBS-008OR	8	5 - 16	350
EBS-010BK	10	7 - 19	350
EBS-010OR	10	7 - 19	350
EBS-012BK	12	8 - 24	300
EBS-012OR	12	8 - 24	300
EBS-015BK	15	10 - 27	250
EBS-015OR	15	10 - 27	250
EBS-020BK	20	14 - 30	200
EBS-020OR	20	14 - 30	200
EBS-025BK	25	18 - 35	200
EBS-025OR	25	18 - 35	200
EBS-030BK	30	20 - 50	150
EBS-030OR	30	20 - 50	150
EBS-040BK	40	30 - 60	100
EBS-040OR	40	30 - 60	100
EBS-045BK	45	35 - 75	100
EBS-045OR	45	35 - 75	100
EBS-050BK	50	40 - 80	100
EBS-050OR	50	40 - 80	100
EBS-064BK	64	45 - 105	100
EBS-064OR	64	45 - 105	100
EBS-076BK	76	60 - 120	100
EBS-076OR	76	64 - 120	100

TECHNICAL SPECIFICATIONS

Material:

Polyester, black or orange

Temperature range:

-50 ~ 150 °C