

NYLON CABLE TIE WITH STAINLESS STEEL LOCK

PART NR.

See dimensions table

COUNTRY OF ORIGIN:

China

STANDARDS:

REACH and RoHS compliant

Flammability: UL94 V-2

ABS

CSA


Lloyd's

UL listed

CHARACTERISTICS:

- For universal use
- Stainless steel locking barb
- Not flammable

PHOTO / TECHNICAL DRAWING



DIMENSIONS

Part nr.	Color	L mm	W mm	Max. bundle mm	Min. Str. in kgs	Pcs/bag
TY-23 m	natural	92	2,40	16,00	8,1	1000
TY-23 mx	UV black	92	2,40	16,00	8,1	1000
TY-232 m	natural	203	2,40	50,00	8,1	1000
TY-232 mx	UV black	203	2,40	50,00	8,1	1000
TY-234 m	natural	356	2,40	102,00	8,1	1000
TY-234 mx	UV black	356	2,40	102,00	8,1	1000
TY-24 m	natural	140	3,60	29,00	18,0	1000
TY-24 mx	UV black	140	3,60	29,00	18,0	1000
TY-242 m	natural	204	3,60	50,00	18,0	1000
TY-242 mx	UV black	204	3,60	50,00	18,0	1000
TY-26 m	natural	284	3,60	76,00	18,0	1000
TY-26 mx	UV black	284	3,60	76,00	18,0	1000
TY-244 m	natural	368	3,60	103,00	18,0	1000
TY-244 mx	UV black	368	3,60	103,00	18,0	1000
TY-25 m	natural	186	4,80	45,00	22,5	1000
TY-25 mx	UV black	186	4,80	45,00	22,5	1000
TY-253 m	natural	295	4,80	78,00	22,5	1000
TY-253 mx	UV black	295	4,80	78,00	22,5	1000
TY-28 m	natural	361	4,80	102,00	22,5	1000
TY-28 mx	UV black	361	4,80	102,00	22,5	1000
TY-272 m	natural	223	6,90	50,00	54,4	500
TY-272 mx	UV black	223	6,90	50,00	54,4	500
TY-27 m	natural	340	6,90	90,00	54,4	500
TY-27 mx	UV black	340	6,90	90,00	54,4	500
TY-29 m	natural	771	6,90	229,00	54,4	500
TY-29 mx	UV black	771	6,90	229,00	54,4	500

TECHNICAL SPECIFICATIONS

Material:

Nylon (PA66)

Locking device:

Stainless steel

Operating temperature:

-60 ~ 85 °C (natural)

-60 ~ 105 °C (black)