

CORRUGATED TUBE - DUAL WALL

PART NR.

See dimensions table

COUNTRY OF ORIGIN

China

STANDARDS

REACH and RoHS compliant

CHARACTERISTICS

- Our corrugated tube is flexible and flame retardant
- It has excellent electrical and physical properties, including excellent acid fastness and corrosion resistance
- Open slot design allows quick and easy installation and later on removal and inspection
- It is typically used in automotive electronics, terminal lugs, small electrical parts, lead wires of toy motors and transformers, etc.
- Great heat resistance
Super cold impact strength
High strength
Bending stability
Excellent chemical resistance

PHOTO / TECHNICAL DRAWING



DIMENSIONS

Part nr.	Nominal size	Inner Ø mm	Outer Ø mm	Thickness mm	Mtrs/reel
2PCT09-025	9	8,9 ± 0,3	13,8 ± 0,3	≥ 0,25	25
2PCT13-025	13	12,8 ± 0,3	18,7 ± 0,3	≥ 0,25	25
2PCT22-025	22	20,0 ± 0,3	25,8 ± 0,3	≥ 0,25	25
2PCT25-025	25	24,8 ± 0,3	31,4 ± 0,3	≥ 0,25	25
2PCT32-025	32	31,4 ± 0,3	41,9 ± 0,3	≥ 0,25	25
2PCT44-025	44	43,3 ± 0,3	54,5 ± 0,3	≥ 0,25	25

TECHNICAL SPECIFICATIONS

Material: PP/PA, black
Temperature range: -40 ~ 135 °C