

**PART NR.**  
See dimensions table

**COUNTRY OF ORIGIN**  
Taiwan

**STANDARDS**  
REACH and RoHS compliant

**ALSO AVAILABLE**

Part nr. 15 mm	Part nr. 19 mm	Color
IST15ASS01	IST19ASS01	1x black, 1x red, 1x green, 1x blue, 1x yellow
IST15ASS02BK	IST19ASS02BK	5x black
IST15ASS02WH	IST19ASS02WH	5x white



**PHOTO / TECHNICAL DRAWING**



**DIMENSIONS**

Part nr. 15 mm	Part nr. 19 mm	Thickness mm	Color	Rolls/wrap
IST15BL	IST19BL	0,1	blue	10
IST15BR	IST19BR	0,1	brown	10
IST15YE	IST19YE	0,1	yellow	10
IST15GS	IST19GS	0,1	grey	10
IST15RD	IST19RD	0,1	red	10
IST15GR	IST19GR	0,1	green	10
IST15WH	IST19WH	0,1	white	10
IST15BK	IST19BK	0,1	black	10
IST15GY	IST19GY	0,1	green/yellow	10

**TECHNICAL SPECIFICATIONS**

Backing:	Plasticized PVC
Glue:	Rubber based adhesive
Peel strength at 180 °C:	To steel > 0.35 kg/25 mm To backing > 0.35 kg/25 mm
Unwind force:	> 350 gr/19 mm
Tensile strength:	> 5 kg/25 mm
Elongation:	> 100 %
Dielectric breakdown:	> 5 kV