

SELF-FUSING TAPE

PART NR.

See dimensions table

COUNTRY OF ORIGIN

Taiwan

STANDARDS

REACH and RoHS compliant

CHARACTERISTICS

- Ideal for waterproof sealing of electrical connections, temporary repair and sealing of plumbing joints
- Suitable for emergency repair of radiators, engine hoses and auto electrics
- Easy to unwind and resistant to water, ozone, UV and a wide range of chemicals including alkalis, hydraulic fluids and vegetable oils
- It is essential that it is completely dry when used but beyond that is safe on any material
- Blank paper core, inner diameter 38 mm

PHOTO / TECHNICAL DRAWING



DIMENSIONS

Part nr.	Liner	Width	Thickness	Length	Rolls/wrap
SFT001	PP synthetic release liner	19 mm	0,75 mm	10 m	10
SFT002	PP synthetic release liner	19 mm	0,75 mm	9,1 m	10
SFT003	PP synthetic release liner	19 mm	0,5 mm	10 m	10

TECHNICAL SPECIFICATIONS

Backing:	Ethylene propylene rubber, black
Release liner:	PP, white
Dielectric strength:	40-45 kV/mm
Tensile strength:	> 2,5 kg
Elongation at break:	> 500 %
Operating temperature:	90 °C continuous, 130 °C peak