

CORRUGATED TUBE - CLOSED

PART NR.

See dimensions table

COUNTRY OF ORIGIN

China

STANDARDS

REACH and RoHS compliant

CHARACTERISTICS

- Our corrugated tube is flexible and flame retardant
- It has excellent electrical and physical properties, including excellent acid fastness and corrosion resistance
- It is typically used in automotive electronics, terminal lugs, small electrical parts, lead wires of toy motors and transformers, etc.
- Great heat resistance
Super cold impact strength
High strength
Bending stability
Excellent chemical resistance

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material:

Temperature range:

PP/PA, black or orange

-40 ~ 135 °C

DIMENSIONS

Part nr.	Nominal size	Inner Ø mm	Outer Ø mm	Mtrs/reel
CCTE04.5-500	4.5	4,5 ± 0,3	6,5 ± 0,3	500
CCTE05-500	5,0	5,0 ± 0,3	8,0 ± 0,3	500
CCT06-100	6,0	6,0 ± 0,3	9,0 ± 0,3	100
CCTE06-500	6.5	6,0 ± 0,3	9,0 ± 0,3	500
CCTE06-100	6.5	6,0 ± 0,3	9,0 ± 0,3	100
CCTE07-500	7,0	7,0 ± 0,3	10,0 ± 0,3	500
CCTE08-500	8,0	8,0 ± 0,3	12,0 ± 0,3	500
CCT09-100	9,0	9,0 ± 0,3	13,0 ± 0,3	100
CCTE09-500	9,0	9,0 ± 0,3	13,0 ± 0,3	500
CCTE09-100	9,0	9,0 ± 0,3	13,0 ± 0,3	100
CCTE10-400	10,0	10,0 ± 0,3	14,0 ± 0,3	400
CCT11-100	11,0	11,0 ± 0,3	15,0 ± 0,3	100
CCTE11-400	11,0	11,0 ± 0,3	15,0 ± 0,3	400
CCTE11-100	11,0	11,0 ± 0,3	15,0 ± 0,3	100
CCTE12-200	12,0	12,0 ± 0,3	16,0 ± 0,3	200
CCT13-100	13,0	13,0 ± 0,3	17,0 ± 0,3	100
CCTE13-200	13,0	13,0 ± 0,3	17,0 ± 0,3	200
CCTE13-100	13,0	13,0 ± 0,3	17,0 ± 0,3	100
CCTE14-200	14,0	14,0 ± 0,3	18,0 ± 0,3	200
CCTE15-200	15,0	15,0 ± 0,3	19,0 ± 0,3	200
CCT16-050	16,0	16,0 ± 0,3	20,0 ± 0,3	50
CCTE16-200	16,0	16,0 ± 0,3	20,0 ± 0,3	200
CCTE16-050	16,0	16,0 ± 0,3	20,0 ± 0,3	50
CCTE17-200	17,0	17,0 ± 0,3	21,0 ± 0,3	200
CCTE18-200	18,0	18,0 ± 0,3	22,0 ± 0,3	200
CCT19-050	19,0	19,0 ± 0,3	23,0 ± 0,3	50

Part nr.	Nominal size	Inner Ø mm	Outer Ø mm	Mtrs/reel
CCTE19-200	19,0	19,0 ± 0,3	23,0 ± 0,3	200
CCTE19-050	19,0	19,0 ± 0,3	23,0 ± 0,3	50
CCTE20-100	20,0	20,0 ± 0,3	24,0 ± 0,3	100
CCTE20-025	20,0	20,0 ± 0,3	24,0 ± 0,3	25
CCTE21-100	21,0	21,0 ± 0,3	25,0 ± 0,3	100
CCT22-025	20,0	22,0 ± 0,3	27,0 ± 0,3	25
CCTE22-100	22,0	22,0 ± 0,3	27,0 ± 0,3	100
CCTE23-100	23,0	23,0 ± 0,3	30,0 ± 0,3	100
CCT25-025	25,0	25,0 ± 0,3	30,0 ± 0,3	25
CCTE25-100	25,0	25,0 ± 0,3	30,0 ± 0,3	100
CCTE25-025	25,0	25,0 ± 0,3	30,0 ± 0,3	25
CCTE26-100	26,0	26,0 ± 0,3	34,0 ± 0,3	100
CCT28-025	28,0	28,0 ± 0,3	34,0 ± 0,3	25
CCTE28-050	28,0	28,0 ± 0,3	34,0 ± 0,3	50
CCTE28-025	28,0	28,0 ± 0,3	34,0 ± 0,3	25
CCT30-025	30,0	30,0 ± 0,3	36,0 ± 0,3	25
CCTE30-050	30,0	30,0 ± 0,3	36,0 ± 0,3	50
CCTE30-025	30,0	30,0 ± 0,3	36,0 ± 0,3	25
CCT32-025	32,0	32,0 ± 0,3	38,0 ± 0,3	25
CCTE32-050	32,0	32,0 ± 0,3	38,0 ± 0,3	50
CCTE32-025	32,0	32,0 ± 0,3	38,0 ± 0,3	25
CCT35-025	35,0	35,0 ± 0,3	40,0 ± 0,3	25
CCTE35-050	35,0	35,0 ± 0,3	40,0 ± 0,3	50
CCTE35-025	35,0	35,0 ± 0,3	40,0 ± 0,3	25
CCT40-025	40,0	40,0 ± 0,3	45,0 ± 0,3	25