

PART NR.

See dimensions table

COUNTRY OF ORIGIN

China

STANDARDS

REACH and RoHS compliant

CHARACTERISTICS

- Our corrugated tube is flexible and flame retardant
- It has excellent electrical and physical properties, including excellent acid fastness and corrosion resistance
- Open slot design allows quick and easy installation and later on removal and inspection
- It is typically used in automotive electronics, terminal lugs, small electrical parts, lead wires of toy motors and transformers, etc.
- Great heat resistance
Super cold impact strength
High strength
Bending stability
Excellent chemical resistance

PHOTO / TECHNICAL DRAWING**DIMENSIONS**

Part nr.	Nominal size	Inner Ø mm	Outer Ø mm	Mtrs/reel
PCT06-100	6	6 ± 0,3	9 ± 0,3	100
PCTE06-100	6	6 ± 0,3	9 ± 0,3	100
PCT09-100	9	9 ± 0,3	13 ± 0,3	100
PCTE09-100	9	9 ± 0,3	13 ± 0,3	100
PCT11-100	11	11 ± 0,3	15 ± 0,3	100
PCTE11-100	11	11 ± 0,3	15 ± 0,3	100
PCT13-100	13	13 ± 0,3	17 ± 0,3	100
PCTE13-100	13	13 ± 0,3	17 ± 0,3	100
PCT16-050	16	16 ± 0,3	20 ± 0,3	50
PCTE16-050	16	16 ± 0,3	20 ± 0,3	50
PCT19-050	19	19 ± 0,3	23 ± 0,3	50
PCTE19-050	19	19 ± 0,3	23 ± 0,3	50
PCT22-025	22	22 ± 0,3	27 ± 0,3	25
PCTE22-025	22	22 ± 0,3	27 ± 0,3	25
PCT25-025	25	25 ± 0,3	30 ± 0,3	25
PCTE25-025	25	25 ± 0,3	30 ± 0,3	25
PCT28-025	28	28 ± 0,3	34 ± 0,3	25
PCTE28-025	28	28 ± 0,3	34 ± 0,3	25
PCT30-025	30	30 ± 0,3	36 ± 0,3	25
PCTE30-025	30	30 ± 0,3	36 ± 0,3	25
PCT32-025	32	32 ± 0,3	38 ± 0,3	25
PCTE32-025	32	32 ± 0,3	38 ± 0,3	25
PCT35-025	35	35 ± 0,3	40 ± 0,3	25
PCTE35-025	35	35 ± 0,3	40 ± 0,3	25
PCT40-025	40	40 ± 0,3	45 ± 0,3	25
PCTE40-025	40	40 ± 0,3	45 ± 0,3	25

TECHNICAL SPECIFICATIONS

Material:

PP/PA, black or orange

Temperature range:

-40 ~ 135 °C