

## EXPANDABLE BRAIDED SLEEVE - BOX

### PART NR.

See dimensions table

### COUNTRY OF ORIGIN

China

### STANDARDS

REACH and RoHS compliant

Halogen free

Flammability: VW-1

UL listed

### CHARACTERISTICS

- Our expandable sleeve is flame retardant and halogen free
- It offers durable abrasion resistance in a wide range of industrial applications
- The open weave structure allows an easy installation on a bundle of hoses or cables, even with bulky or large size
- Totally expanded sleeve can reach at least 1.5 times of the initial dimension
- It is ideal for application in wire harnesses, automatic equipment, railway and general manufacturing industry, where wire and cable are required to have a robust and durable protection
- Cutting tool: hot knife

### PHOTO / TECHNICAL DRAWING



### DIMENSIONS

Part nr.	Nom. size mm	Bundle range mm	Mtrs/reel
EBSB-003BK	3	1 - 6	1000
EBSB-003OR	3	1 - 6	1000
EBSB-006BK	6	3 - 9	500
EBSB-006OR	6	3 - 9	500
EBSB-008BK	8	5 - 16	350
EBSB-008OR	8	5 - 16	350
EBSB-010BK	10	7 - 19	350
EBSB-010OR	10	7 - 19	350
EBSB-012BK	12	8 - 24	300
EBSB-012OR	12	8 - 24	300
EBSB-015BK	15	10 - 27	250
EBSB-015OR	15	10 - 27	250
EBSB-020BK	20	14 - 30	200
EBSB-020OR	20	14 - 30	200
EBSB-025BK	25	18 - 35	200
EBSB-025OR	25	18 - 35	200
EBSB-030BK	30	20 - 50	150
EBSB-030OR	30	20 - 50	150
EBSB-040BK	40	30 - 60	100
EBSB-040OR	40	30 - 60	100
EBSB-045BK	45	35 - 75	100
EBSB-045OR	45	35 - 75	100
EBSB-050BK	50	40 - 80	100
EBSB-050OR	50	40 - 80	100

### TECHNICAL SPECIFICATIONS

Material:

Polyester, black or orange

Temperature range:

-50 ~ 150 °C