

## SINGLE LIP FIXING CLAMP - SL SERIES W1

### PART NR.

See dimensions table

### COUNTRY OF ORIGIN

Netherlands

### STANDARDS

REACH and RoHS compliant

DIN 2768-vL

### CHARACTERISTICS

- Fixing clamps affix hoses, pipes and cables to their proper places. It is also known as duct clamp. The rubber part of the band absorbs vibration and prevents cable damage, while having an added insulating effect. This clamp may also be used without the rubber lining, e.g. when they are intended to conduct electricity
- Mainly used on air, fluid, gas and steam lines and also suitable for low pressure hydraulic applications. The absence of a screw mechanism allows these clips to be useful on extremely small hoses

### PHOTO / TECHNICAL DRAWING



### DIMENSIONS

### TECHNICAL SPECIFICATIONS

Material:

Mild steel, all parts zinc plated

Lining:

Rubber, shore hardness 65±5°C

Fastening:

M6 screw

Part nr.	Min Ø	Max Ø	Band width mm	Fastening	Packed
MPC1-13045006	3,20	4,80	13,0	M6	50
MPC1-13055008	4,80	6,40	13,0	M6	50
MPC1-13075010	6,40	7,90	13,0	M6	50
MPC1-13085011	7,90	9,50	13,0	M6	50
MPC1-13095012	9,50	11,10	13,0	M6	50
MPC1-13115014	11,10	12,70	13,0	M6	50
MPC1-13125015	12,70	14,30	13,0	M6	50
MPC1-13135016	14,30	15,90	13,0	M6	50
MPC1-13145017	15,90	17,50	13,0	M6	50
MPC1-13155018	17,50	19,00	13,0	M6	50
MPC1-13165019	19,00	20,60	13,0	M6	50
MPC1-13175020	20,60	22,20	13,0	M6	50
MPC1-13185021	22,20	23,80	13,0	M6	50
MPC1-13195022	23,80	25,40	13,0	M6	50
MPC1-13205023	25,40	27,00	13,0	M6	50
MPC1-13215024	27,00	28,60	13,0	M6	50
MPC1-13245027	28,60	30,20	13,0	M6	50
MPC1-13265029	30,20	31,80	13,0	M6	50
MPC1-13275030	31,80	33,30	13,0	M6	50
MPC1-13285031	33,30	34,90	13,0	M6	50
MPC1-13295032	34,90	36,50	13,0	M6	10
MPC1-13345037	36,50	38,10	13,0	M6	10
MPC1-13395042	38,10	41,00	13,0	M6	10