

WORMDRIVE HOSE CLAMP - ST SERIES W1

PART NR.

See dimensions table

COUNTRY OF ORIGIN

Netherlands

STANDARDS

REACH and RoHS compliant
SS 2998, DIN3017-1

CHARACTERISTICS

- This strong wormdrive clamp is suitable for high torque loads and complies with standard SS 2298. This clamp is not only very robust, but it will also last much longer compared to classic electroplating protection. The band with rolled-up edges ensures perfect clamping on the hose without damaging it. The compact screw and ratchet assembly and also the housing made from a drawn tube make this clamp highly torsion-resistant. The hexagonal head C7 allows standard tools to be used for mounting and removal
- For agricultural applications, automotive industry and aftermarket, industrial sector hardware, DIY

PHOTO / TECHNICAL DRAWING



DIMENSIONS

TECHNICAL SPECIFICATIONS

Material:
Fastening:

Mild steel, all parts zinc plated
7 mm hex head

Part nr.	Adjustment mm	Max. advised torque Nm	Band width mm	Band thickness mm	Packed
BHC1-0814	8 - 14	3,0	9,0	0,5 - 1	50
BHC1-1117	11 - 17	3,0	9,0	0,5 - 1	50
BHC1-1320	13 - 20	3,0	9,0	0,5 - 1	50
BHC1-1525	15 - 25	5,0	12,0	0,5 - 1	50
BHC1-1929	19 - 29	5,0	12,0	0,5 - 1	50
BHC1-2232	22 - 32	5,0	12,0	0,5 - 1	50
BHC1-2638	26 - 38	5,0	12,0	0,5 - 1	50
BHC1-3244	32 - 44	5,0	12,0	0,5 - 1	50
BHC1-3850	38 - 50	5,0	12,0	0,5 - 1	50
BHC1-4456	44 - 56	5,0	12,0	0,5 - 1	50
BHC1-5065	50 - 65	5,0	12,0	0,5 - 1	50
BHC1-5875	58 - 75	5,0	12,0	0,5 - 1	50
BHC1-6885	68 - 85	5,0	12,0	0,5 - 1	10
BHC1-7795	77 - 95	5,0	12,0	0,5 - 1	10
BHC1-87112	87 - 112	5,0	12,0	0,5 - 1	10
BHC1-104138	104 - 138	5,0	12,0	0,5 - 1	10
BHC1-130165	130 - 165	5,0	12,0	0,5 - 1	10
BHC1-155180	155 - 180	5,0	12,0	0,5 - 1	10
BHC1-175205	175 - 205	5,0	12,0	0,5 - 1	10
BHC1-200231	200 - 231	5,0	12,0	0,5 - 1	10
BHC1-226256	226 - 256	5,0	12,0	0,5 - 1	10
BHC1-251282	251 - 282	5,0	12,0	0,5 - 1	10
BHC1-277307	277 - 307	5,0	12,0	0,5 - 1	10
BHC1-302325	302 - 325	5,0	12,0	0,5 - 1	10
BHC1-321350	321 - 350	5,0	12,0	0,5 - 1	10
BHC1-346375	346 - 375	5,0	12,0	0,5 - 1	10
BHC1-371400	371 - 400	5,0	12,0	0,5 - 1	10
BHC1-396425	396 - 425	5,0	12,0	0,5 - 1	10
BHC1-421450	421 - 450	5,0	12,0	0,5 - 1	10