

PART NR.
RSPU101
RSPU102

red
yellow

COUNTRY OF ORIGIN
Netherlands


STANDARDS
REACH and RoHS compliant
ISO 7375/2 1998
ISO 7628/2 1998
DIN 73378/02 '96
DIN 74310-2 / 12 '93, '91
DIN 74323/04 and DIN 74324/02 '96

CHARACTERISTICS

- Very good recovery from kinks
- Longer working lengths
- High tensile elasticity
- Oil, petrol, ozone and UV resistant
- Much higher flexibility at low temperatures
- Very good abrasion and tear resistance (no breakage at the connections)
- Within a temperature range from -40°C to 70°C, the material has the properties of rubber

PUR BLX S AIR BRAKE SPIRAL COILS - STEEL M16 X 1,5

PHOTO / TECHNICAL DRAWING



RSPU101



RSPU102

DIMENSIONS

L x W x H:	8 x 2 x 12 mm
Working length:	4 m
Number of turns:	21 ± 2
Closed coil outer Ø:	75 +10/-0 mm
Closed coil inner Ø:	50 +10/-0 mm
Tail lengths:	150 ± 10 mm

TECHNICAL SPECIFICATIONS

Material:	Polyurethane, red or yellow
Connection:	M16 x 1,5 mm, male
Anti kink protection:	Zinc plated steel
Working pressure:	10 Bar
Min. burst pressure:	40 Bar
Operating temperature:	-40 ~ 70 °C