

PART NR.

RSPU103

RSPU104

red

yellow

COUNTRY OF ORIGIN

Netherlands

STANDARDS

REACH and RoHS compliant

ISO 7375/2 1998

ISO 7628/2 1998

DIN 73378/02 '96


DIN 74310-2 / 12 '93, '91

DIN 74323/04 and DIN 74324/02 '96

CHARACTERISTICS

- Very good recovery from kinks
- Longer working lengths
- High tensile elasticity
- Oil, petrol, ozone and UV resistant
- Much higher flexibility at low temperatures
- Very good abrasion and tear resistance (no breakage at the connections)
- Within a temperature range from -40°C to 70°C, the material has the properties of rubber

PHOTO / TECHNICAL DRAWING



RSPU103



RSPU104

DIMENSIONS

L x W x H:	8 x 2 x 12 mm
Working length:	4 m
Number of turns:	21 ± 2
Closed coil outer Ø:	75 +10/-0 mm
Closed coil inner Ø:	50 +10/-0 mm
Tail lengths:	150 ± 10 mm
Connection:	M22 x 1,5 mm, male

TECHNICAL SPECIFICATIONS

Material:	Polyurethane, red or yellow
Anti kink protection:	Zinc plated steel
Working pressure:	10 Bar
Min. burst pressure:	40 Bar
Operating temperature:	-40 ~ 70 °C